

Angle ledge tray delivery & storage cabinet, standard & heavy duty, non-insulated, aluminum

390-A Meyer Circle, Corona, California 92879-1078

Phone (951) 340-3419

Fax (951) 340-2716

- Standard duty cabinet for holding, storing or delivering food in various stages in 18x26" sheet pans. Also available in heavy duty models.
- Stays sanitary with routine steam cleaning.
- N.S.F. listed.

These cabinets allow bottom of the tray instead of the bead to ride on the angle ledge with standard 3" spacing. Top & bottom are extra strong, heli-arc welded to the frame with additional reinforcing on the inside. Each cart comes with horizontal stabilizing bar to prevent "racking". Other features include:

- Top: Made from inner & outer panels each 0.063'' thick.
- Bottom: 0.190" thick formed into one piece.
- Sides: 0.063" thick with 1½"x1¾"x0.075" thick angle ledge slides spaced on 3" centers.
- Uprites: 2"x1"x0.125" specially extruded channels.
- Back: 0.063'' aluminum.
- **Door:** 0.080'' aluminum hemmed at all four sides with stainless steel hinges & gravity latch.
- Casters: 5"x1 1/4" deluxe, N.S.F. approved, all swivel.



SPECIFIED

SPACING ON CENTERS

ALUMINUM ANGLE LEDGE SUPPORTS



Model 9156-HD-1820

ADDITIONAL FEATURES FOR HEAVY DUTY MODELS:

- **Back:** 0.080'' aluminum, brake formed into "C" section at ends with extra reinforcement in the middle.
- **Door:** 0.080'' brake formed reinforced vertically in the middle with 1'' square tubing. Furnished with heavy duty latch.

| Туре | Model No. | *Pan Capacity (18″x26″) | Overall Dimension (Inches) | | | Shipping |
|------------------|--------------|-------------------------------|----------------------------|------------|-------------|-----------------|
| | | | A Width | B Depth | C Height | Weight (pounds) |
| Standard Duty | 9156-1820 | 20 | 22 | 301/8 | 69% | 124 |
| | 9156-1816 | 16 | 22 | 301/8 | 57% | 114 |
| | 9156-1812 | 12 | 22 | 301/8 | 45% | 104 |
| Heavy Duty | 9156-HD-1820 | 20 | 22 | 301//8 | 69% | 129 |
| | 9156-HD-1816 | 16 | 22 | 301/8 | 57% | 119 |
| | 9156-HD-1812 | 12 | 22 | 301/8 | 45% | 109 |

*Cabinets also available for different capacity and with spacing other than 3". Consult factory.

Super Duty Models:

Double reinforced door, double tie rods and back reinforced with additional bracing (³/₁₅" thick) fitted around rear uprites. For this style, add "-SD" after standard duty model numbers.

Options:

- 1. Four corner bumpers.
- 2. Wrap around bumper.
- 3. Swing door catch.
- 4. Lockable latch.
- Wheel brakes.
- 6. Poly casters.
- 7. Door tag holder.
- 8. Stainless steel construction.