

## Hot insulated double & triple door cabinets for insulated trays for correctional facilities

390-A Meyer Circle • Corona, CA 92879-1078 • Phone (951) 340-3419 • Fax (951) 340-2716 • www.sammonsequipment.com

- Fully insulated heated cabinets for correctional facilities.
- Maintains prepared meals in insulated trays stacked on removable tubular shelves at desired serving temperature.
- Heavy duty welded s/s construction.
- Offered in double and triple section style for 11"x16"x2 3/4" and 13 7/8"x15 1/2"x 2 1/2" thk. insulated trays.

These hot cabinets are furnished with 1 1/2" fiberglass insulation and removable flat square tubing shelves for stacking insulated trays. Cabinets roll easily on 6" casters, 2 with brakes. **The bottom mounted heating unit** is easily removable (non-removable optional) & provides the necessary gentle & forced air circulation with thermostatically controlled temperature.

Outer body, door & top are made of 20 ga. (18 ga. optional) polished stainless steel for strength & durability. Inners are made of 22 ga. s/s. Push handle, perimeter bumper, tamper resistant fasteners, heavy duty reinforced correctional hinges, latches and through the door type dial thermometer are standard.

#### HE-1600 Heating Unit:

1600 W heating coil, 1,675W total, 13.96 amps at 120 VAC 60 HZ single phase furnished with 15 amps, 8ft. long cord with 3 prong Nema 5-15 P grounding plug, off-on switch, 75W blower, thermostat and pilot lights. Unit has over 4 quarts capacity water reservoir. Blower and heating coils are thermally protected. Optional 220-240V available. **Optional HE-2000 heating unit** with 2000W heating coil and 20 amps cord and 5-20P plug for \*20 amps service is also available (standard for triple door cabinet). Consult factory.

\*For Canadian application HE-2000 and HE-1600 are furnished with 30 amps/20amps cord and plug respectively.



2285-HIN-2-1116-60  
(shown with correctional package)



Model Number	Tray Size (Inches)	Type of Door	Tray Capacity	O.A. Dimensions (Inches)			Weight (Pounds)
				D	W	H	
2285-HIN-2-1116-44	11x16x2 3/4 (T-140) SEE NOTE 2	Double	44	31 1/2	48 1/2	52 3/8	405
2285-HIN-2-1116-52		Double	52	31 1/2	48 1/2	58 3/8	430
2285-HIN-2-1116-60		Double	60	31 1/2	48 1/2	64 3/8	450
2285-HIN-3-1116-68		Triple	68	31 1/2	69 3/4	52 3/8	490
2285-HIN-3-1116-90		Triple	90	31 1/2	69 3/4	60	580
2285-HIN-3-1116-98		Triple	98	31 1/2	69 3/4	64 3/8	596
2285-HIN-2-1315-48	13 7/8 x 15 1/2 x 2 1/2 (ALLADIN) SEE NOTE 3	Double	48	37 1/4	48 1/2	52 3/8	390
2285-HIN-2-1315-56		Double	56	37 1/4	48 1/2	58 3/8	460
2285-HIN-3-1315-80		Triple	80	37 1/4	69 3/4	52 3/8	625
2285-HIN-3-1315-92		Triple	92	37 1/4	69 3/4	60	650



2285-HIN-3-1116-90  
(with correctional package)

**NOTE 1:** These cabinets are also available without the heating unit and for other tray sizes. Consult factory.

**NOTE 2:** These models for 11"x16"x2 3/4" trays will also carry Duralux T-240 (11 1/4"x15 1/2"x2 2/5" thk), Incellator #2 & 3 (10"x16"x2.15" or 2.85" thk), Plastocon (10 3/4"x14 1/2"x2 1/2" or 3 1/4" thk) and Rock (9 1/2"x14 1/4"x1 7/8" thk) trays. Capacity will vary. Consult factory.

**NOTE 3:** These models for 13 7/8"x15 1/2"x2 1/2" will NOT go thru' a standard 33"W door. Please make sure that your hallway door openings are larger than 38" for these carts. These models will also carry design specialty T-340 (13 3/8"x15 1/8"x2 9/16" thk) and Plastocon (Insulator & Supermax 13.6"x15"x2.86" thk) trays. Capacity will vary. Consult factory.

**NOTE 4:** Sample tray is required with order for proper sizing. Aluminum construction is also available. Consult factory.

#### ADDITIONAL CORRECTIONAL PACKAGE (OPTIONAL)

1. Non-removable heating unit (in lieu of removable)
2. Heavy duty side/top mounted security lockable latch
3. 18 ga. s/s exterior
4. 6" balloon casters (in lieu of std 6")
5. Extra set of hinges (3 sets in lieu of 2 sets) for each door
6. 8" polyurethane or 8" balloon casters

**Better food service equipment – standard models and custom designs.**

**C-25**