

## Hot insulated single door cabinets for insulated trays for correctional facilities

390-A Meyer Circle • Corona, CA 92879-1078 • Phone (951) 340-3419 • Fax (951) 340-2716 • www.sammonsequipment.com

- Fully insulated heated cabinets for correctional facilities.
- Maintains prepared meals in insulated trays stacked on removable tubular shelves at desired serving temperature.
- Heavy duty welded s/s construction with reinforced hinges.
- Offered for 11"x16"x2 3/4" and 13 7/8"x15 1/2"x 2 1/2" thk. and other insulated trays.
- Choice of top or bottom mounted 1600W heating unit.

These hot cabinets are furnished with 1 1/2" fiberglass insulation and removable flat square tubing shelves for stacking insulated trays. Cabinets roll easily on 5" casters, 2 with brakes. **The top or bottom mounted heating unit** is easily removable (non-removable optional) & provides the necessary gentle & forced air circulation with thermostatically controlled temperature.

Outer body, door & top are made of 20 ga. (18 ga. optional) polished stainless steel for strength & durability. Inners are made of 22 ga. s/s. Perimeter bumper, tamper resistant fasteners, heavy duty reinforced correctional hinges, latches and dial thermometer are standard.

**\*HE-1600 Bottom Mounted Heating Unit: (for STYLE "A" cabinets)**

1600 W heating coil, 1,675W total, 13.96 amps at 120 VAC 60 HZ single phase furnished with 15 amps, 8ft long cord with 3 prong Nema 5-15 P grounding plug, off-on switch, 75W blower, thermostat and pilot lights. Unit has over 4 quarts capacity water reservoir. Blower and heating coils are thermally protect protected.

**\*HET 1600 Top Mounted Heated Unit: (for STYLE "B" cabinets)**

Same electrical characteristics as HE-1600 except it uses two (2) 75 W blowers and is rated at 1750W total, 14.58 amps. Optional HE-2000/HET-2000 heating units with 2000W heating coil and 20 amps cord and 5-20P plug for 20 amps service and 220-240V application are also available. Consult factory.

For Canadian application HE-1600/HET-1600 are furnished with 20 amps cord and plug and HE-2000/HET-2000 are furnished with 30 amps cord and plug.



STYLE "A"  
2285-HIN-1116-42  
(with bottom mounted heating unit)



**STYLE "A": Cabinets with bottom mounted heating unit supplied with removable tubular shelves for stacking trays.**

Model Number	Tray Size (Inches)	Tray Spacing (Inches)	Tray Capacity	O.A. Dimensions (Inches) D x W x H	Weight (Pounds)
2285-HIN-1116-42	11 x 16 x 2 3/4	Stacked	42	38 3/8 x 31 1/2 x 60 1/2	380
2285-HIN-1116-21	11 x 16 x 2 3/4	Stacked	21	38 3/8 x 31 1/2 x 43	363
2285-HIN-1315-30	13 7/8 x 15 1/2 x 2 1/2	Stacked	30	38 3/8 x 29 x 60 1/2	375
2285-HIN-1315-16	13 7/8 x 15 1/2 x 2 1/2	Stacked	16	38 3/8 x 29 x 43	350



STYLE "B"  
2286-HIN-1116-45  
(with top mounted heating unit)

**STYLE "B": Cabinets with top mounted heating unit supplied with removable tubular shelves for stacking trays.**

Model Number	Tray Size (Inches)	Tray Spacing (Inches)	Tray Capacity	O.A. Dimensions (Inches) D x W x H	Weight (Pounds)
2286-HIN-1116-45	11 x 16 x 2 3/4	Stacked	45	38 3/4 x 31 1/2 x 62 1/2	410
2286-HIN-1116-36	11 x 16 x 2 3/4	Stacked	36	38 3/4 x 31 1/2 x 53 1/2	398
2286-HIN-1315-32	13 7/8 x 15 1/2 x 2 1/2	Stacked	32	38 3/4 x 28 1/4 x 62 1/2	396
2286-HIN-1315-26	13 7/8 x 15 1/2 x 2 1/2	Stacked	26	38 3/4 x 28 1/4 x 52 1/2	380

**NOTE 1:** These cabinets are also available without the heating unit and for other tray sizes. Consult factory.

**NOTE 2:** These models for 11"x16"x2 3/4" trays will also carry Duralux T-240 (1 1/4"x15 1/2"x2 2/5" thk), Incellator #2 & 3 (10"x16"x2.15" or 2.85" thk), Plastocon (10 3/4"x14 1/2"x2 1/2" or 3 1/4" thk) and Rock (9 1/2"x14 1/4"x1 7/8" thk) trays. Capacity will vary. Consult factory.

**NOTE 3:** These models for 13 7/8"x15 1/2"x2 1/2" will also carry design specialty T-340 (13 3/8"x15 1/8"x2 9/16" thk) and Plastocon (Insulator & Supermax 13.6"x15"x2.86" thk) trays. Capacity will vary. Consult factory.

**NOTE 4:** Sample tray is required with order for proper sizing. Aluminum construction is also available. Consult factory.

**ADDITIONAL CORRECTIONAL PACKAGE (OPTIONAL)**

1. Non-removable heating unit (in lieu of removable)
2. Heavy duty side/top mounted security lockable latch
3. 6" or 8" polyurethane or balloon casters (in lieu of std 5")
4. Extra set of hinges (3 sets in lieu of 2 sets) for each door
5. 18 ga. s/s exterior
6. Aluminum construction