

Undercounter heated cabinets, insulated & non-insulated

390-A Meyer Circle • Corona, CA 92879-1078 • Phone (951) 340-3419 • Fax (951) 340-2716 • www.sammonsequipment.com

These **undercounter cabinets** provide excellent holding capacity for 18" x 26" Bun Pans and/or 12" x 20" steam pans depending upon the model selected. Easy lift out racks for insulated models allow fast clean up as necessary. Heavy duty chrome plated or stainless steel hinges and positive latch provide easy opening and closing of door. Insulated aluminum models use 0.190" thick deck & 0.063" thick body & stainless steel models use 22 ga. inner and 20 ga. outer body, 1 ½" thick fiberglass insulation and silicone gasket. Off-on switch, power light, thermometer, thermostat and 14/3 ga. cord with molded plug for 15 amps, 120v, 60hz service are also standard. Slides in universal angle type cabinets are adjustable on 1 ½" centers. Choice of two different types of heating is offered. Other options are listed below.

Undercounter heated cabinets insulated & non-insulated with bottom mounted heating unit

- Choice of aluminum or s/s models
- · Choice of insulated or non-insulated models
- Circulating heat with blower motor

Furnished with HE-1600 heating unit with 15 amps cord & NEMA 5-15P plug. 3" casters are standard.

Power Requirements: Total 1675 watts on 110-120 volts. 60 hz, Single Phase, A.C.

Туре	Model Number		Type of	Pan Size	Pan	Pan Spacing	O.A. Dimensions (Inches)			Weight (Pounds)	
	Aluminum	Stainless Steel	Slide	(Inches)	Capacity	(Inches)	W	D	Н	Alum	S/S
Insulated	9292-HIN-1205-UC	2292-HIN-1205-UC	Channel	**12 x 20	5	23/4	$21^{1}/_{16}$	333/8	32	156	225
	9282-HIN-1805-UC	2282-HIN-1805-UC	Angle	18x26	5	3	27	333/8	32	175	235
	9252-HIN-1808-UC	2252-HIN-1808-UC	Channel	18x26	8	11/2	27	333/8	32	180	240
	*9282-HIN-LA-5-UC	*2252-HIN-LA-5-UC	*Angle	*18x26	5	3	27	333/8	32	180	239
	9232-HIN-UA-5-UC	2232-HIN-UA-5-UC	Universal	18x26	5	3	29	361/8	32	220	280
			Angle	**12x20	10						
Non-Insulated	9250-H-1810-UC	2250-H-18,10-UC	Extruded	18x26	10	11/2	22	301/8	313/8	90	160
	9280-H-1805-UC	2280-H-1805-UC	Angle	18x26	5	3	22	301/8	313/8	88	166
	9280-H-UA-5-UC	2280—H-UA-5-UC	Universal Angle	18x26	5	3	25	301/8	313/8	110	195
				** 12x20	10						
	9250-H-1208-UC	2250-H-1208-UC	Extruded	**12 x 20	8	3	25	30½	313/8	102	192



9292-HIN-1205-UC (shown with optional 5" casters)



9250-H-1810-UC (shown with optional 5" casters)

Undercounter heated insulated cabinets, with radiant heating system and top mounted controls



- Choice of aluminum or s/s models.
- Furnished with 3" casters. 15 Amps, 120V service.








Pan O.A. Dimensions Weight Model Number Pan Size Pan Spacing (Inches) (Pounds) (Inches) Capacity (Inches) Alum. W D Η Alum S/S 9803-C-1806-UC 2803-C-1806-UC 18 x 26 3 27 325/8 32 134 210 *9803-C-1806-LA-UC *2803-C-1806-LA-UC *18 x 26 *6 3 27 325/8 32 162 240 9803-C-1812-UC 2803-C-1812-UC 18×26 12 11/2 325/8 32 156 236 12 x 20x2½ 9803-C-1206-UC 2803-C-1206-UC 174 3 22 275/8 32 119 6 9803-C-UA-6-UC 2803-C-UA-6-UC 18 x 26 3 291/2 325/8 32 192 270 (Universal (Universal $12x20x2\frac{1}{2}$ Angle Type) Angle Tyne)

^{*}This model is furnished with large angle slides & can also carry 6 steam pans (12"x 20"x 2½") in lieu of 18"x 26". For Options see below.



Options:

A. 4" or 5" casters

B. Pass thru' style (door in the rear)

C. Corner bumpers

Options:

D. Lexan ® glass door

E. Brakes on casters

F. Correctional package

Options:

G. Stationary legs (in lieu of casters)

H. 220V/240V service

I. Perimeter bumper

C-31

^{*} This model is furnished with large angle slides & can also carry 5 steam pans (12"x 20"x 2½") in lieu of 18"x 26". ** 2½" Deep pans. **NOTE:** These cabinets are also available as "proof" only or as hot/proof combination cabinets. Consult factory. For Options see below.