



### Hot insulated single, double & triple door cabinets for 12"x 20" steam pans

- Fully insulated hot s/s cabinets.
- Bottom mounted 1600W heating unit with 15 amps cord & NEMA 5-15P plug (2000W heating unit for 20 amps service optional, standard for 3 door cabinets)
- Welded s/s rack.
- 6" casters, push handle & perimeter bumper are standard.

CATALOG PAGE C-20

Model Number	Pan Spacing (Inches)	Type of Door	** Tray Capacity	O.A. Dimensions (Inches) D x W x H	Weight (Pounds)	List Price (see note)
2292-HIN-1211	2¾	SINGLE	11	31½ x 26 x 50¾	230	\$6,859
2292-HIN-1215	2¾	SINGLE	15	31½ x 26 x 62	246	7,418
2292-HIN-2-1222	2¾	DOUBLE	22	31½ x 44 x 52¾	310	8,818
2292-HIN-2-1230	2¾	DOUBLE	30	31½ x 44 x 64¾	390	9,466
2292-HIN-3-1250	2¾	TRIPLE	50	31½ x 64½ x 64¾	546	14,109



**2292-HIN-1230**  
(with correctional package)

\*\*Tray capacity is based on 2 ½" deep pans. Cabinets will also accommodate 4" & 6" deep pans. Capacity will vary. Consult factory. Correctional package available. Consult factory.  
NOTE: Prices are based on a minimum quantity of 5 units. For other options, see Table CC-1

### Hot insulated cabinet with top mounted heating unit & single door for compartment trays

- Fully insulated cabinet.
- Top mounted 1600W heating unit HET-1600 with 15 amps cord & NEMA 5-15P plug.
- Welded s/s rack.
- 5" casters.

CATALOG PAGE C-18

Model Number	Tray Size (Inches)	Tray Spacing (Inches)	Capacity	O.A. Dimensions (Inches) D x W x H	Weight (Pounds)	List Price (see note)
2286-HIN-2-810-78	8½ x 10 x 1¼	3	78	36¾ x 29½ x 62½	430	\$7,881
2286-HIN-2-810-90	8½ x 10 x 1¼	3	90	36¾ x 29½ x 70½	490	8,099
2286-HIN-1015-26	10¾ x 15 x 1¾	3	26	36¾ x 26¼ x 62½	410	7,461
2286-HIN-1015-30	10¾ x 15 x 1¾	3	30	36¾ x 26¼ x 70½	475	7,806



**2286-HIN-1015-30**

Correctional package is available. See page PC-4 & for other options, see Table CC-1.  
Cabinets are also available for other tray sizes. Consult factory.  
(with optional package)  
NOTE: Prices are based on a minimum quantity of 5 units.

### Dual cavity hot/ambient insulated cabinet for compartment trays

- Left section ambient
- Right section heated
- Fully insulated
- Bottom mounted 2000W heating unit for 20 amps service. (15 amps with 1600W heating optional).

CATALOG PAGE C-18

Model Number	Tray Size (Inches)	Tray Spacing (Inches)	Tray Capacity		O.A. Dimensions (Inches) W x D x H	Weight (Pounds)	List Price (see note)
			Hot	Ambient			
2285-HIN-1-1-2828-1015	10¾ x 15 x 1¾	3	28	28	31½ x 48½ x 64¾	370	\$9,791
2285-HIN-1-1-2020-1015	10¾ x 15 x 1¾	3	20	20	31½ x 48½ x 52¾	320	9,507
2285-HIN-2-2-5656-910	9 x 10½ x 2½	3	56	56	31½ x 66 x 64¾	495	11,457
2285-HIN-2-2-4040-910	9 x 10½ x 2½	3	40	40	31½ x 66 x 52¾	420	11,179



**2285-HIN-1-1-2828-1015**  
(with options)

**Options**  
List Options  
Cold cartridge for ambient section.....\$617  
Both sides heated with separate 1600W heating units.....P.O.R. (consult factory).  
NOTE: Prices are based on a minimum quantity of 5 units.  
For other options, see Table CC-1



**TABLE CC-1  
OPTIONS FOR PROOFER & HOT CABINETS**

	LIST PRICE FOR	
	ALUMINUM MODELS	STAINLESS STEEL MODEL
1. Corner bumpers (set of 4)	\$129	\$141
2. Vertical leg bumpers (set of 4)	152	167
3. Wheel brakes (pair) for 5" or 6" casters	52	52
4. Wrap around bumper (single section cabinet)	233	265
5. Wrap around bumper (double section cabinet)	293	349
6. Floor lock (5")	162	216
7. Floor lock (6")	186	243
8. Floor lock (8")	253	308
9. Extra pair of universal angle slides	87	145
10. <u>CASTERS UPGRADE (IN LIEU OF 5" STANDARD, SET OF 4)</u>		
A. 5" Polyurethane	102	102
B. 5" Balloon (decorative)	129	129
C. 6" Polyurethane (1,200# capacity)	159	159
D. 6" Heavy duty polyurethane (2,000# capacity)	243	243
E. 5" Hi-Temp	191	191
F. 6" Balloon	245	245
G. 8" Polyurethane	273	273
H. Stationary legs	243	243
11. <u>CASTERS UPGRADE (IN LIEU OF 6" STANDARD, SET OF 4)</u>		
A. 6" Balloon	204	204
B. 8" Balloon	340	340
C. 8" Polyurethane	216	216
12. Swing door catch (for each door)	91	108
13. Door tag holder (for each door)	52	82
14. Lockable latch (for each door)	110	129
15. Top mounted latch (for each door)	211	260
16. Push handle (each)	144	186
17. Push handle (each) with 2 donut bumpers	186	236
18. Solid dutch doors (non-insulated) in lieu of single solid door	234	305
19. Solid dutch doors (insulated) in lieu of single solid door	297	486
20. Single LEXAN <sup>®</sup> door in lieu of single solid door	334	409
21. Dutch LEXAN <sup>®</sup> doors in lieu of single solid door	614	735
22. Dutch LEXAN <sup>®</sup> doors in lieu of single LEXAN <sup>®</sup> door	243	308
23. *Single pass thru' door in the rear	476	607
24. *Dutch pass thru' doors in the rear	594	1,065
25. 220v/240v application (in lieu of 120v)	223	223
26. Canadian application (in lieu of U.S.)	199	199
27. 17 hour timer (in lieu of 10 hour)	125	125
28. HE-2000 (2,000w heating, 20 amps service unit) in lieu of HE-1600 (1,600w heating, 15 amps service unit)	159	159
29. Bail handles/pair/ side	125	174

\*FOR HOT INSULATED CABINETS WITH TOP MOUNTED HEATING UNITS ONLY.

**NOTE:** Most aluminum hot, proof & hot/proof cabinets are also available in s/s construction. Add 65% to list prices of aluminum models unless listed otherwise based on a minimum quantity of 5 units & an up charge of 20% to 80% may apply for quantities under 5. Consult factory.