



## Hot universal angle slide cabinets, insulated & non-insulated

(Also See Note 3)

CATALOG PAGES C-7 & C-8


Furnished with HE-2000 heating unit with 20 amps cord & NEMA 5-20P plug. 5" casters are standard.  
 Power Requirements: Total 2075 watts on 110-120 volts. 60 hz, Single Phase, A.C.

### Aluminum Heated Cabinets with Universal Angle Slides (also see notes 3 & 4)

Type	Model Number (Also see note 3)	Tray Capacity (Note 1 & 2)	Pan Spacing (Inches)	O.A. Dimensions (Inches)			Weight (Pounds)	List Price
				W	D	H		
Non-Insulated	9230-H-UA-9	9	4½	26	31	59½	160	\$3,187
	9230-H-UA-10	10	4½	26	31	65½	170	3,403
	9230-H-UA-11	11	4½	26	31	70	185	3,485
Insulated	9232-HIN-UA-9	9	4½	29½	36¼	60½	265	4,326
	*9232-HIN-DD-UA-12	12	4½	29½	36¼	72½	295	4,641



9230-H-UA-9



9232-HIN-DD-UA-12

### Stainless Steel Heated Cabinets with Universal Angle Slides (also see notes 3 & 4)

Type	Model Number (Also see note 3)	Tray Capacity (Note 1 & 2)	Pan Spacing (Inches)	O.A. Dimensions (Inches)			Weight (Pounds)	List Price
				W	D	H		
Non-Insulated	2230-H-UA-9	9	4½	26	31	59½	252	P.O.R.
	2230-H-UA-11	11	4½	26	31	70	280	\$4,689
Insulated	2232-HIN-UA-9	9	4½	29½	36¼	60½	378	5,724
	2232-HIN-UA-12	12	4½	29½	36¼	72½	402	6,223
	*2232-HIN-DD-UA-12	12	4½	29½	36¼	72½	410	6,435

\*Furnished with dutch doors as standard on this model.

**NOTE 1:** Tray capacity is shown for 18"x 26" bun pans. Capacity for 12"x 20" steam pans/gastronorm (GN1/1) pans (2½" or 4" high) or 14"x 18" trays is twice the number.

**NOTE 2:** Slides are adjustable on 1½" (38mm) centers. Each universal slide set can carry one (1) each 18"x 26" bun pan or 20"x 20" baking pan or 530mm x 650mm gastronorm (GN2/1) pan or 20"x 20" glass rack or two (2) each 12"x 20" steam pans or 325mm x 530mm gastronorm (GN1/1) pan or 14"x 18" trays or 10"x 20" roasting pans or 13¾"x 20¾" school lunch baskets.

**NOTE 3:** These cabinets are also available as proofing cabinets in lieu of hot cabinets at no extra charge or as hot/proof combination cabinets at an additional price of \$335. Replace "-H" by "-P" in model number for proofing cabinets or replace "-H" by "-HP" for hot/proof combination cabinets.

**NOTE 4:** Hot insulated cabinets can also be furnished with 1600w heating unit (HE-1600) for 15 amps service instead of standard 2000w heating unit (HE-2000) at no extra charge. Consult factory. For other options, see Table CC-1.

## Small heated cabinets insulated & non-insulated


Furnished with HE-1600 heating unit with 15 amps cord & NEMA 5-15P plug. 5" casters are standard.  
 Power Requirements: Total 1675 watts on 110-120 volts. 60 hz, Single Phase, A.C.

### Small Heated Cabinets CATALOG PAGE C-12

Type	Model Number		Type of Slide	Pan Size (Inches)	Pan Capacity	Pan Spacing (Inches)	O.A. Dimensions (Inches)			Weight (Pounds)		List Price	
	Aluminum	Stainless Steel					W	D	H	Alum	SS	Alum	SS
Insulated	9292-HIN-1208	2292-HIN-1208	Channel	*12x20	8	2¼	20½	32½	42	90	185	PRICE ON REQUEST	
	9282-HIN-1808	2282-HIN-1808	Angle	18x26	8	3	26	35½	42	96	198		
	9252-HIN-1816	2252-HIN-1816	Extruded	18x26	16	1½	26	35½	42	102	208		
	9232-HIN-1805	2232-HIN-1805	Universal Angle	18x26	5	4½	29	30¼	42	110	230		
12x20				10									
Non-Insulated	9250-H-1810	-	Extruded	18x26	10	1½	22	30¼	33¼	65	-		
	9280-H-1805	2280-H-1805	Angle	18x26	5	3	22	30¼	33¼	60	130		
	9280-H-1807	2280-H-1807	Angle	18x26	7	3	22	30¼	39¼	67	142		
	9250-H-1208	-	Extruded	*12x20	8	3	25	30¼	33¼	69	-		

\*2½" Deep pans.

**NOTE:** These cabinets are also available as "proof" only or as hot/proof combination cabinets. See NOTE 3 above.



9292-HIN-1208



9250-H-1810



**TABLE CC-1  
OPTIONS FOR PROOFER & HOT CABINETS**

	LIST PRICE FOR	
	ALUMINUM MODELS	STAINLESS STEEL MODEL
1. Corner bumpers (set of 4)	\$129	\$141
2. Vertical leg bumpers (set of 4)	152	167
3. Wheel brakes (pair) for 5" or 6" casters	52	52
4. Wrap around bumper (single section cabinet)	233	265
5. Wrap around bumper (double section cabinet)	293	349
6. Floor lock (5")	162	216
7. Floor lock (6")	186	243
8. Floor lock (8")	253	308
9. Extra pair of universal angle slides	87	145
10. <u>CASTERS UPGRADE (IN LIEU OF 5" STANDARD, SET OF 4)</u>		
A. 5" Polyurethane	102	102
B. 5" Balloon (decorative)	129	129
C. 6" Polyurethane (1,200# capacity)	159	159
D. 6" Heavy duty polyurethane (2,000# capacity)	243	243
E. 5" Hi-Temp	191	191
F. 6" Balloon	245	245
G. 8" Polyurethane	273	273
H. Stationary legs	243	243
11. <u>CASTERS UPGRADE (IN LIEU OF 6" STANDARD, SET OF 4)</u>		
A. 6" Balloon	204	204
B. 8" Balloon	340	340
C. 8" Polyurethane	216	216
12. Swing door catch (for each door)	91	108
13. Door tag holder (for each door)	52	82
14. Lockable latch (for each door)	110	129
15. Top mounted latch (for each door)	211	260
16. Push handle (each)	144	186
17. Push handle (each) with 2 donut bumpers	186	236
18. Solid dutch doors (non-insulated) in lieu of single solid door	234	305
19. Solid dutch doors (insulated) in lieu of single solid door	297	486
20. Single LEXAN <sup>®</sup> door in lieu of single solid door	334	409
21. Dutch LEXAN <sup>®</sup> doors in lieu of single solid door	614	735
22. Dutch LEXAN <sup>®</sup> doors in lieu of single LEXAN <sup>®</sup> door	243	308
23. *Single pass thru' door in the rear	476	607
24. *Dutch pass thru' doors in the rear	594	1,065
25. 220v/240v application (in lieu of 120v)	223	223
26. Canadian application (in lieu of U.S.)	199	199
27. 17 hour timer (in lieu of 10 hour)	125	125
28. HE-2000 (2,000w heating, 20 amps service unit) in lieu of HE-1600 (1,600w heating, 15 amps service unit)	159	159
29. Bail handles/pair/ side	125	174

\*FOR HOT INSULATED CABINETS WITH TOP MOUNTED HEATING UNITS ONLY.

**NOTE:** Most aluminum hot, proof & hot/proof cabinets are also available in s/s construction. Add 65% to list prices of aluminum models unless listed otherwise based on a minimum quantity of 5 units & an up charge of 20% to 80% may apply for quantities under 5. Consult factory.